

AN APPARATUS FOR SUPPLYING A THERAPEUTIC OXYGEN GAS

## BACKGROUND OF THE INVENTION

## 5           1.    Field of the Invention

The invention relates to an apparatus for supplying a therapeutic oxygen gas.

## 2.    Description of the Related Art

10           In treatments for respiratory system diseases such as pulmonary emphysema or chronic bronchitis, oxygen inhalation is known as one of the most effective treatments. In oxygen inhalation therapy, a therapeutic oxygen gas, such as oxygen gas or an oxygen enhanced gas which may be produced by separating nitrogen gas from  
15           air, is supplied to the patient with a therapeutic oxygen gas supplying apparatus.

Conventional therapeutic oxygen gas supplying apparatuses supply a therapeutic oxygen gas intermittently, in synchronization with the respiration  
20           of a patient, at a constant volume for each respiration. The respiratory frequency, however, is not constant. When the respiratory frequency is increased, in particular when tachypnea is presented, if the therapeutic oxygen gas supplying apparatus supplies the  
25           therapeutic oxygen gas at a constant volume for each respiration, dyspnea will result.

## SUMMARY OF THE INVENTION

The invention is directed to solve the prior art problems, and to provide an apparatus for supplying a  
30           therapeutic oxygen gas improved to change the volume for each respiration in accordance with the respiratory frequency.

According to the invention, there is provided an apparatus for supplying a therapeutic oxygen gas. The  
35           apparatus comprises a cylinder for containing pressurized therapeutic oxygen gas, a nasal cannula, adapted to be introduced into a nasal passage of a patient, and a

FOUO-SECRET

conduit extending between the cylinder and the nasal cannula for directing the therapeutic oxygen gas to the nasal cannula from the cylinder. A pressure sensor is provided on the conduit for detecting the pressure in the conduit. A valve is provided on the conduit, which allows and blocks the fluid communication between the cylinder and the nasal cannula. A controller controls the operation of the valve in synchronization with the respiration of a patient based on the changes in the pressure detected by the pressure sensor. The volume of the therapeutic oxygen gas passing through the valve for each respiration is increased, compared with a normal respiration condition, when the respiratory frequency increases.

#### DESCRIPTION OF THE DRAWINGS

These and other objects and advantages and further description will now be discussed in connection with the drawings in which:

Figure 1 is a block diagram of a therapeutic oxygen gas supplying apparatus according to an embodiment of the invention;

Figure 2 is a flow chart showing an algorithm of determining the time period for opening the solenoid operated valve; and

Figure 3 is graph which shows the volume of the therapeutic oxygen gas supplied to a patient, the volume increasing in steps according to an increase in respiratory frequency.

#### Description of the Preferred Embodiments

With reference to Figure 1, a therapeutic oxygen gas supplying apparatus 10 according an embodiment of the invention supplies a therapeutic oxygen gas, pure oxygen gas or an oxygen enhanced gas, to a patient (not shown) from an oxygen gas cylinder 12 through a conduit 18 and a nasal cannula 16 attached to the face of the patient. The conduit 18 comprises a flexible tube which is, at one of the ends, attached to a shut-off valve 14, connected

to the oxygen cylinder 12, and, at the other end, to an inlet port 16a of the nasal cannula 16. The nasal cannula 16 provides means for introducing the therapeutic oxygen gas and includes a pair of cannula portions 16b which are adapted to be introduced into the nasal passages of the patient.

A pressure regulating valve 20 and an orifice 22 are provide on the conduit 18 downstream of the shut-off valve 14. Downstream of the orifice 22, a solenoid operated valve 24 is provided. The pressure regulating valve 20 and an orifice 22 regulate the pressure in the conduit 18 upstream of the solenoid operated valve 24 at a predetermined pressure. The solenoid operated valve 24 includes a solenoid 24a for moving the solenoid operated valve 24 between a first and a second position. At the first position, the solenoid operated valve 24 blocks the flow of the therapeutic oxygen gas, and at the second position, the solenoid operated valve allows the therapeutic oxygen gas to flow therethrough. A pressure sensor 26 is provided on the conduit 18 downstream of the solenoid operated valve 24. The pressure sensor 26 can be any kind of pressure sensor which provides an electric signal representing the pressure in the conduit 18. Preferably, the pressure sensor 26 comprises an electrostatic capacity type pressure sensor having a capacitor of which the capacitance changes in response to the changes in the pressure in the conduit 18.

The apparatus 10 further comprises a controller 30 for controlling the operation of the solenoid operated valve 24 in synchronization with the respiration of the patient. The controller 30 includes an A/D converter 32, a counter 34, a microcomputer 50, an input device 36, a solenoid driver 38 and a display 40. The microcomputer 50 includes CPU (central processing unit) 52, ROM (read-only memory) 54, RAM (random-access memory) 56, an input port 36 and an output ports 60, which are connected to each other through a bidirectional bus 62. The A/D

5

10

15

20

25

30

35

initiation of a respiration.

When the microcomputer 50 detects the initiation of a respiration, the microcomputer 50 generates a valve open command to the solenoid driver 38. When the solenoid driver 38 receives the valve open command, the solenoid driver 38 energizes the solenoid 24a to move the solenoid operated valve 24 to the second position whereby the valve 24 opens to allow the oxygen therapeutic gas to flow therethrough. The microcomputer 50 generates the valve open command for a valve opening time long enough to provide the patient with a predetermined volume of the oxygen therapeutic gas prescribed by a doctor, as described below.

Figure 2 is a flow chart showing an algorithm of determining the time period for opening the solenoid operated valve 24. After the activation of the apparatus 10, in step S10, an initialization is carried out wherein the following parameters are input to the microcomputer 50 with the input device 36.

- 20  $R_n$ : respiratory frequency when the respiration of the patient is normal condition (BPM (breaths par minute))
- $R_a$ : a first threshold value for respiratory frequency larger than  $R_n$ (BPM)
- 25  $R_b$ : a second threshold value for respiratory frequency larger than  $R_a$ (BPM)
- $F_0$ : flow rate of oxygen therapeutic gas which may be prescribed by a doctor ( $m^3/min$ )

In step 10, time period  $\tau$  (minutes) for opening the solenoid operated valve 24 is calculated by the flowing equation.

$$\tau = F_0 / \alpha R_n f_0 \dots (1)$$

where:

- $\alpha$ : non-dimensional constant
- 35  $f_0$ : flow rate of oxygen therapeutic gas through the solenoid operated valve 24 when the valve 24 is open

under the predetermined pressure in the conduit 18  
upstream of the valve 24 ( $\text{m}^3/\text{min}$ )

The non-dimensional constant  $\alpha$  is an inverse of  
ratio of the time period of inhalation relative to the  
5 time period of one respiration, and it can be 3 since the  
I/E ratio is generally 1/2. If the I/E ratio is not 1/2,  
the non-dimensional constant  $\alpha$  can be altered,  
accordingly.

The time period  $\tau$  thus obtained means a time period  
10 for opening the solenoid operated valve 24 sufficient for  
the volume of the oxygen therapeutic gas, which may be  
prescribed by a doctor, to flow through the valve 24  
during inhalation of normal condition.

In steps S12 and S14, the initiation of respiration  
15 is determined by monitoring the changes in the pressure,  
as described above. In step S16, the microcomputer 50  
calculates the respiratory frequency  $R$  by measuring the  
time interval between initiations of sequential tow  
respirations. In step S18, the respiratory frequency  $R$   
20 is compared with the first threshold value  $R_a$  which is  
larger than the respiratory frequency  $R_n$  under the normal  
respiration condition. If  $R$  is equal to or smaller than  
 $R_a$  ("No" at the step S18), then the respiration is  
determined as normal, and the time period  $\tau$  is decided,  
25 in step 22, as valve opening time  $T_{vo}$  for actually  
opening the solenoid operated valve 24. If  $R$  is larger  
than  $R_a$  ("Yes" at the step S18), then, in step S20,  $R$  is  
further compared with the second threshold value  $R_b$ . If  
 $R$  is equal to or smaller than  $R_b$  ("Yes" at the step S20),  
30 then, the respiration is determined as mild tachypnea,  
and  $\tau_{xa}$  is decided, in step 24, as the valve opening time  
 $T_{va}$ . Here "a" is a predetermined constant larger than 1,  
and can, for example, be 1.25. If  $R$  is larger than  $R_b$   
("No" at the step S20) then the respiration is determined  
35 as heavy tachypnea, and  $\tau_{xb}$  is decided, in step 26, as

the valve opening time  $T_{vo}$ . Here "b" is a predetermined constant larger than "a", and can, for example, be 1.50.

The microcomputer generates a valve opening command to the solenoid driver 38 for the valve opening time  $T_{vo}$ .

Therefore, the volume of the oxygen therapeutic gas supplied to the patient for each respiration increases in steps according to the increase in the respiratory frequency, as shown in Figure 3. In Figure 3,  $V_n$  indicates the volume of the therapeutic oxygen gas supplied for each respiration under the normal respiration condition,  $V_a$  indicates the volume when the respiratory frequency is above  $R_a$ , and  $V_b$  indicates the volume when the respiratory frequency is above  $R_b$ .

15 It will also be understood by those skilled in the art that the foregoing description is a preferred embodiment of the disclosed device and that various changes and modifications may be made without departing from the spirit and scope of the invention.